

CONTINENTAL


Tel +380 62 3111510, 3352459, Fax +380 62 3370855 info@continental.dn.ua www.continental.dn.ua/lang/en/

To: Purchase Department
From: Continental, Ukraine

Dear Sirs,


We are Ukrainian company and we offer Steel Fiber for steel-fibro-concrete.
Steel fiber is produce according CE Declaration of Conformity for EU.

Steel Fiber with anchors




Type	Diameter, mm	Length L, mm	Height H, mm	Anchors length E, mm
50/1,0	1,0+/-0,1	50,0+/-3,0	3,1+/-0,5	5,0+/-1,0
60/1,0	1,0+/-0,1	60,0+/-5,0	3,0+/-0,5	5,0+/-1,0
60/0,9	0,9+/-0,09	60,0+/-5,0	2,9+/-0,5	5,0+/-1,0
60/0,8	0,8+/-0,08	60,0+/-5,0	2,9+/-0,5	5,0+/-1,0
60/0,75	0,75+/-0,07	60,0+/-5,0	2,9+/-0,5	5,0+/-1,0
30/0,75	0,75+/-0,07	30,0+/-3,0	2,9+/-0,5	5,0+/-1,0
30/0,55	0,55+/-0,05	30,0+/-3,0	2,9+/-0,5	5,0+/-1,0

Wavy Steel Fiber



Type	Diameter, mm	Length L, mm	Height H, mm	Wave length, mm
50/1,0	1,0+/-0,1	50,0+/-5,0	2,0+/-0,6	8,0+/-0,1
50/1,3	1,3+/-0,13	50,0+/-5,0	2,0+/-0,6	8,0+/-0,1

Steel Fiber with flattened ends



Type	Diameter, mm	Length L, mm	Width of flattened ends, mm	Length of flattened ends and transition zone, mm
50/1,0	1,0+/-0,1	50,0+/-5,0	2,0+/-3,0	5,0+/-1,0

Material: Cold-drawn low-carbon steel wire, without coating, GOST 3282, tensile strength of 900-1450 N/mm². Other geometrical sizes can be made on the concordance with a customer's order.

Packing Into cardboard boxes of 25 kg, on 1200x1000 mm wood pallets.

We offer also:

- **Low-carbon steel wire GOST 3282-74** (without heat treatment and heat treatment) diam. from 0,8 mm to 2,0 mm;
 - **Steel welding wire SV08G2S**, GOST 2246-70 (not coating and copper coating) diam. from 0,8 mm to 2,0 mm;
- Wire is delivered in 200-500 kg weight coils or in 10-30 kg bundles.

Best regards,

Continental
Sergey Mirgorod

Tel +380 62 3111510, 3352459

Fax +380 62 3370855 e-mail: info@continental.dn.ua

<http://www.continental.dn.ua/lang/en/>